

Spindle Shapers

New Range of Spindle Moulders



The Holytek 525 Series Spindle Shaper delivers precise and vibration-free shaping performance.

Powered by a 7.5 HP motor (optional), the HS-525TS model with sliding table & tilting spindle will give you more flexible functions and precision shaping operations with minimum trouble.

HS-525TS

HOLYTEK

HOLYTEK 525 series Spindle Moulder



HS-525MS
(W / Sliding table)



HS-525T
(W / Tilting spindle)



HS-525M
(Fixed Table)

FEATURES

INTERCHANGEABLE SPINDLES:

Choose from five spindle diameters: 3/4", 1", 1-1/4", 30mm and 35mm. The spindle has MK5 taper, thereby assuring precision fitting.

QUICK CHANGE SPINDLE SPEED:

Spindle speeds of 3,000, 4,500, 6,000, 7,500 and 10,000 rpm can be achieved, driven by a four-speed pulley. By simply loosening a lock lever and shifting the assembly, the speed may be changed quickly and efficiently.

SPECIFICATIONS

MODEL	HS-525M, MS		HS-525T, TS	
Spindle dia. for choice	1", 1-1/4", 30mm, 35mm			
Spindle speed	3,000, 4,500, 7,500, 10,000 rpm			
Taper of spindle	MK5			
Spindle motor	5 HP, 7.5 HP (option)			
Spindle travel	130mm			
Tilting angle	-		-5° ~ 90° ~ +45°	
Max. table insert diameter	8-5/8" (220mm)			
Table size	27-1/2" x 35-1/2" (700 x 900mm)			
Table height	35-1/2" (900mm)			
Sliding table size	(35-1/2" x 9") 900 x 230mm			
Sliding table travel	32-1/2" (830mm)			
Fence size	4-15/16" x 35-1/2" (125 x 900mm)			
N.W.	336 kgs	358 kgs	336 kgs	358 kgs
G.W.	408 kgs	436 kgs	408 kgs	436 kgs
Packing dimensions (cm)	107(L) x 71(W) x 127(H)		107(L) x 107(W) x 127(H)	

* Specifications and design characteristics are subject to change without prior notice.

VERSIBLE SPINDLE ROTATION:

The double-locked spindle guarantees safe rotation in both clockwise and counter-clockwise directions.

TWO TABLE INSERTS : (6-3/8", 8-5/8")

FENCE:

All cast aluminum alloy fence with micro adjustment knob and precise size.

OPTIONAL FOR ROUTING SPINDLE

HOLYTEK

HOLYTEK INDUSTRIAL CORP.

9F-1, NO. 400, SEC. 1, CHANG PING RD., TAICHUNG, TAIWAN, R.O.C.
TEL: 886-4-2245-2818 (REP.) FAX: 886-4-2243-6928

E-mail: holytek@ms13.hinet.net
http://www.holytek.com.tw